

(19) World Intellectual Property
Organization
International Bureau



552141

(43) International Publication Date
21 October 2004 (21.10.2004)


PCT

(10) International Publication Number
WO 2004/089163 A1

- (51) International Patent Classification⁷: **A47C 1/032** (74) Agent: **PIOVESANA, Paolo**; Corso del Popolo, 70, I-30172 Venezia Veneto (IT).
- (21) International Application Number: **PCT/EP2004/002975** (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 22 March 2004 (22.03.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: **VE2003A000014** 10 April 2003 (10.04.2003) IT
- (71) Applicant (for all designated States except US): **IMARC S.P.A.** [IT/IT]; Via Meucci, 21, I-36028 Rossano Veneto (IT).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **LIVIERO, Stefano** [IT/IT]; Via Meucci, 21, I-36028 Rossano Veneto (IT).
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: **DEVICE FOR ADJUSTING THE DEGREE OF PRELOAD OF THE SPRINGS IN OFFICE CHAIR MECHANISMS**



(57) Abstract: A device for adjusting the degree of preload of springs in office chair mechanisms which comprise at least two parts hinged together and elastic means (30) maintaining said parts elastically spaced apart, said device being characterised by comprising: -a first element (36) provided with at least one inclined surface (40) and coupled to one of the parts (to the elastic means), -a second element (42) provided with at least one appendix interacting with the inclined surface (40) of the first element, and coupled to the elastic means (to one of the parts), - means (46, 48) for inducing axial rotation of one of said elements, - means (54, 56) for blocking the rotation of the other element.

WO 2004/089163 A1



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*